(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property **Organization** International Bureau





(43) International Publication Date 29 July 2004 (29.07.2004)

(10) International Publication Number WO 2004/063612 A2

(51) International Patent Classification7:

F16L

(21) International Application Number:

PCT/EP2004/001017

(22) International Filing Date: 8 January 2004 (08.01.2004)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data: 0300140

8 January 2003 (08.01.2003) FR

(71) Applicant (for all designated States except US): CAR-BONE LORRAINE COMPOSANTS [FR/FR]; 41, Rue Jean Jaurès, 92231 Genevilliers (FR).

(72) Inventors; and

- (75) Inventors/Applicants (for US only): POTIER, Alexandre [FR/FR]; 33bis, rue Jean Jaurès, 92231 Genevilliers (FR). BERGER, Dominique [FR/FR]; 14 allée Claude Monet, 95370 Montigny Les Cormeilles (FR). BOM-MIER, Christophe [FR/US]; 17 Oxbow Lane, Basking Ridge, NJ 07290 (US). RAYMOND, Olivier [FR/FR]; 6bis rue Léon Hutin, 93220 Cagny (FR). DE WASCH, Jérôme [FR/FR]; 33 rue Jean Jaurès, 92231 Genevilliers (FR).
- (74) Agent: FENOT, Dominique; Pechiney, 217, Cours Lafayette, F-69451 Lyon Cédex 06 (FR).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Declarations under Rule 4.17:

- as to the applicant's entitlement to claim the priority of the earlier application (Rule 4.17(iii)) for all designations
- of inventorship (Rule 4.17(iv)) for US only

Published:

without international search report and to be republished upon receipt of that report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: THERMAL INSULATION STRUCTURES COMPRISING LAYERS OF EXPANDED GRAPHITE PARTICLES COM-PRESSED TO DIFFERENT DENSITIES AND THERMAL INSULATION ELEMENTS MADE FROM THESE STRUCTURES

(57) Abstract: Thermal insulation structure comprising at least one flexible layer based on compressed expanded graphite particles characterised in that the density of the said flexible layer is equal to at least 0.4 g/cm3 (400 kg/m³) and in that the said thermal insulation structure also comprises another layer close to the said flexible layer based on compressed graphite particles with a lower density, typically less than 0.4 g/cm³ (400 kg/m³). Preferably, the dense compressed expanded graphite layer has a density of between 0.5 and 1.6 g/cm³ (500 and 1600 kg/m³) and the said sub-dense compressed expanded graphite layer has a density of between 0.05 and 0.3 g/cm³ (50 and 300 kg/m³). Thermal insulation elements are also described that are designed to be fitted on furnaces operating under non-oxidising atmosphere and at temperatures of more than 800°C.

